

NOTICE OF REVISION (NOR)		1. DATE (YYMMDD) 95-10-20		Form Approved OMB No. 0704-0188			
THIS REVISION DESCRIBED BELOW HAS BEEN AUTHORIZED FOR THE DOCUMENT LISTED.							
Public reporting burden for this collection is estimated to average 2 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503. PLEASE DO NOT RETURN YOUR COMPLETED FORM TO EITHER OF THESE ADDRESSES. RETURN COMPLETED FORM TO THE GOVERNMENT ISSUING CONTRACTING OFFICER FOR THE CONTRACT/ PROCURING ACTIVITY NUMBER LISTED IN ITEM 2 OF THIS FORM.				2. PROCURING ACTIVITY NO.			
				3. DODAAC			
4. ORIGINATOR		b. ADDRESS (Street, City, State, Zip Code) Defense Supply Center Columbus 1507 Wilmington Pike Dayton, OH 45444-5270		5. CAGE CODE 67268			
a. TYPED NAME (First, Middle Initial, Last)				7. CAGE CODE 67268			
				6. NOR NO. 5962-R144-95			
				8. DOCUMENT NO. 81006			
9. TITLE OF DOCUMENT Microcircuits, Linear, CMOS, High Level Analog Switches With Drivers, Monolithic Silicon			10. REVISION LETTER		11. ECP NO. 81006ECP-1		
						a. CURRENT F	b. NEW G
12. CONFIGURATION ITEM (OR SYSTEM) TO WHICH ECP APPLIES All							
13. DESCRIPTION OF REVISION							
<p>Sheet 1: Revisions Itr column; add "G". Revisions description column; add "Changes in accordance with NOR 5962-R144-95". Revisions date column; add "95-10-20". Revision level block; add "G". Rev status of sheets; for sheet 1, 2, 3, 8, 9, and 10, add "G".</p> <p>Sheet 2: 1.2.2, under case outline letter add "X", under descriptive designator add "CDFP3-14" under terminals add "14", under package style add "flat pack". Revision level block; add "G".</p> <p>Sheet 3: 1.3, Power dissipation, delete "Case A at $T_A = +125C$" and substitute "Case A and X at $T_A = +125C$". Revision level block; add "G".</p> <p>Sheet 8: Figure 1, Terminal connections, delete "device types 02, 10, and 19, case "E", diagram and substitute the following;</p> <div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> <p><u>Device types 02 and 10</u></p> <p>Case outline E</p> </div> <div style="text-align: center;"> <p><u>Device type 19</u></p> <p>Case outline E</p> </div> </div> <p style="text-align: center;">Continued on following page.</p>							
14. THIS SECTION FOR GOVERNMENT USE ONLY							
a. (X one)		(1) Existing document supplemented by the NOR may be used in manufacture. (2) Revised document must be received before manufacturer may incorporate this change. (3) Custodian of master document shall make above revision and furnish revised document.					
						X	
b. ACTIVITY AUTHORIZED TO APPROVE CHANGE FOR GOVERNMENT DESC-ELDS			c. TYPED NAME (First, Middle Initial, Last) Michael A. Frye				
d. TITLE Chief, Microelectronics Branch		e. SIGNATURE Michael A. Frye		f. DATE SIGNED (YYMMDD) 95-10-20			
15a. ACTIVITY ACCOMPLISHING REVISION DESC-ELDS		b. REVISION COMPLETED (Signature) Marcia B. Kelleher		c. DATE SIGNED (YYMMDD) 95-10-20			

Sheet 8: Revision level block; add "G".

Sheet 9: Figure 1, Terminal connections, delete "device type 04 only, case A", diagram and substitute the following;



Device type 04
Case outline A

Figure 1, Terminal connections, delete "device types 12 and 22, case E and case 2", diagram and substitute the following;

Device types 04, 12, and 22
Case outline E Case outline 2

Revision level block; add "G".

Sheet 10: Figure 1, Terminal connections, delete "device type 06 only, case A", diagram and substitute the following;



Device type 06
Case outline A and X

Figure 1, Terminal connections, delete "device types 14 and 20, case E and case 2", diagram and substitute the following;

Device types 06, 14, and 20
Case outline E Case outline 2


Revision level block; add "G".

REVISIONS																			
LTR	DESCRIPTION										DATE (YR-MO-DA)				APPROVED				
F	Add peak current to absolute maximum ratings. Editorial changes throughout.										92-11-24				M. A. Frye				
THE ORIGINAL FIRST PAGE OF THIS DRAWING HAS BEEN REPLACED.																			
CURRENT CAGE CODE 67268																			
REV																			
SHEET																			
REV																			
SHEET																			
REV STATUS OF SHEETS				REV		F	F	F	F	F	F	F	F	F	F	F	F	F	F
				SHEET		1	2	3	4	5	6	7	8	9	10	11	12	13	
PMIC N/A				PREPARED BY Donald Osborne						DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444									
STANDARDIZED MILITARY DRAWING THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE AMSC N/A				CHECKED BY D. A. DiCenzo															
				APPROVED BY N. A. Hauck															
				DRAWING APPROVAL DATE 81-10-01															
				REVISION LEVEL F															
								SIZE A		CAGE CODE 14933				81006					
				SHEET 1		OF				13									

1. SCOPE

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices".

1.2 Part or Identifying Number (PIN). The complete PIN shall be as shown in the following example:



1.2.1 Device type(s). The device type(s) shall identify the circuit function as follows:

Device type	Generic number	Circuit function
01	IH5040, DG5140	One-channel, 75 ohms, SPST switch
02	IH5041, DG5141	Two-channel, 75 ohms, SPST switch
03	IH5042, DG5142	One-channel, 75 ohms, SPDT switch
04	IH5043, DG5143	Two-channel, 75 ohms, SPDT switch
05	IH5044, DG5144	One-channel, 75 ohms, DPST switch
06	IH5045, DG5145	Two-channel, 75 ohms, DPST switch
07	IH5046	One-channel, 75 ohms, DPDT switch
08	IH5047	One-channel, 75 ohms, 4PST switch
09	IH5140, HI5040	One-channel, 75 ohms, SPST switch
10	IH5141, HI5041	Two-channel, 75 ohms, SPDT switch
11	IH5142, HI5042	One-channel, 75 ohms, SPDT switch
12	IH5143, HI5043	Two-channel, 30 ohms, SPDT switch
13	IH5144, HI5044	One-channel, 30 ohms, DPST switch
14	IH5145, HI5045	Two-channel, 75 ohms, DPST switch
15	HI5046	One-channel, 75 ohms, DPDT switch
16	IH5047, HI5047	One-channel, 75 ohms, 4PST switch
17	HI5046A	One-channel, 30 ohms, DPDT switch
18	HI5047A	One-channel, 30 ohms, 4PST switch
19	IH5148, HI5048	Two-channel, 30 ohms, SPST switch
20	IH5149, HI5049	Two-channel, 30 ohms, DPST switch
21	IH5150, HI5050	One-channel, 30 ohms, SPDT switch
22	IH5151, HI5051	Two-channel, 30 ohms, SPDT switch

1.2.2 Case outline(s). The case outline(s) shall be as designated in MIL-STD-1835 and as follows:

Outline letter	Descriptive designator	Terminals	Package style
A	GDFP5-F14 or CDFP6-F14	14	Flat pack
E	GDIP1-T16 or CDIP2-T16	16	Dual-in-line
I	MACY1-X10	10	Can
2	CQCC1-N20	20	Square leadless chip carrier

1.2.3 Lead finish. The lead finish shall be as specified in MIL-M-38510. Finish letter "X" shall not be marked on the microcircuit or its packaging. The "X" designation is for use in specifications when lead finishes A, B, and C are considered acceptable and interchangeable without preference.

STANDARDIZED
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

81006

REVISION LEVEL
F

SHEET
2

1.3 Absolute maximum ratings.

V ⁺ - V ⁻	33 V dc
V ⁺ - V _D	30 V dc
V _D - V ⁻	30 V dc
V _D - V _S	±22 V dc
V _L - V ⁻	33 V dc
V _L - V _{IN}	30 V dc
V _L - V _R	20 V dc
V _{IN} - V _R	20 V dc
V _R - V ⁻	33 V dc
V _R - V _{IN}	2 V dc
Current (any terminal except S or D)	30 mA
Peak current (source to drain) ^{1/}	80 mA
Storage temperature range	-65° C to +150° C
Lead temperature (soldering, 10 seconds)	+300° C
Junction temperature (T _J)	+175° C
Power dissipation, (P _D) ^{2/} :	
Case A at T _A = +125° C	350 mW
Case E at T _A = +125° C	400 mW
Case I at T _A = +125° C	350 mW
Case 2 at T _A = +125° C	350 mW

1.4 Recommended operating conditions.

+V _{CC}	+15 V dc
-V _{CC}	-15 V dc
V _R	0 V dc
V _L	5 V dc
Ambient operating temperature range (T _A)	-55° C to +125° C
Thermal resistance, junction-to-case (Θ _{JC})	See MIL-STD-1835

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and bulletin. Unless otherwise specified, the following specification, standards, and bulletin of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARDS

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.
MIL-STD-1835 - Microcircuit Case Outlines.

BULLETIN

MILITARY

MIL-BUL-103 - List of Standardized Military Drawings (SMD's).

(Copies of the specification, standards, and bulletin required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

^{1/} Pulse at 1 ms, 10 percent duty cycle maximum.

^{2/} For T_C = +100° C to +125° C, derate linearly at 12 mW/° C.

**STANDARDIZED
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444**

SIZE
A

81006

REVISION LEVEL
F

SHEET
3

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Case outline(s). The case outline(s) shall be in accordance with 1.2.2 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.3 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in table I and shall apply over the full ambient operating temperature range.

3.3.1 Switch operation. The analog switches listed below are guaranteed to turn "on" with either a "low" input ($V_R \leq V_{IL} \leq 0.8$ V) or "high" input ($2.4 \text{ V} \leq V_{IH} \leq V_{IL}$) as specified below (see figure 1).

Device types	V_{IN}	Channels ON	Channels OFF
01, 09	2.4 V dc 0.8 V dc	1	1
02, 10,	2.4 V dc 0.8 V dc	1, 2	1, 2
03, 05, 11, 13, 17, 18	2.4 V dc 0.8 V dc	1 2	2 1
04, 12, 19	2.4 V dc 0.8 V dc	1, 2 3, 4	3, 4 1, 2
07, 15, 21	2.4 V dc 0.8 V dc	2, 3 1, 4	1, 4 2, 3
06, 08, 14, 16, 20, 22	2.4 V dc 0.8 V dc	1, 2, 3, 4	1, 2, 3, 4

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are described in table I.

3.5 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked as listed in MIL-BUL-103 (see 6.6 herein).

3.6 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-BUL-103 (see 6.6 herein). The certificate of compliance submitted to DESC-EC prior to listing as an approved source of supply shall affirm that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.7 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

STANDARDIZED MICROCIRCUIT DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		81006
		REVISION LEVEL F	SHEET 4

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions -55°C ≤ T _A ≤ +125°C, V _{CC} = ±15 V unless otherwise specified		Group A subgroups	Device type	Limits		Unit
						Min	Max	
Drain source "ON" resistance	R _{DS}		V _D = -10 V I _S = 10 mA	1, 3	1 through 16		75	Ω 1/
				2			150	
				1, 3	17 through 22		45	
				2			50	
			V _D = 10 V I _S = -10 mA	1, 3	1 through 16		75	
				2			150	
				1, 3	17 through 22		45	
				2			50	
		V _{CC} = ±10 V 2/	V _D = -7.5 V I _S = 10 mA	1, 3	All		75	
				2			150	
			V _D = 7.5 V I _S = -10 mA	1, 3	All		75	
				2			150	
Channel "ON" leakage current	I _{D(ON)}	(See 3.3.1 for V _{IN})	V _S = V _D = 10 V	2, 3	All	-200	200	nA
				1		-2	2	
			V _S = V _D = -10 V	2, 3	All	-200	200	
				1		-2	2	
			V _S = -10 V V _D = 10 V	2, 3	All	-100	100	
				1		-1	1	
Drain "OFF" leakage current	I _{D(OFF)}	(See 3.3.1 for V _{IN})	V _S = 10 V V _D = -10 V	2, 3	All	-100	100	
				1		-1	1	
			V _S = -10 V V _D = 10 V	2, 3	All	-100	100	
				1		-1	1	
			V _S = 10 V V _D = 10 V	2, 3	All	-100	100	
				1		-1	1	

See footnotes at end of table.

STANDARDIZED
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

REVISION LEVEL
F

81006

SHEET
5

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions $-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$, $V_{CC} = \pm 15\text{ V}$ unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Input current, input voltage low	I_{IL}	$V_{IN} = 0\text{ V}$	1, 3	All	-1	1	μA
			2		-10	1	
Input current, input voltage high	I_{IH}	$V_{IN} = 2.4\text{ V}, 5\text{ V}$	1, 3	All	-1	1	μA
			2		-1	10	
Positive supply current	$+I_{CC}$	$V_{IN} = 0\text{ V}, 5\text{ V}$	1, 3	1 through 8		10	μA
			2			100	
			1	9 through 22		200	
			2, 3			300	
Negative supply current	$-I_{CC}$	$V_{IN} = 0\text{ V}, 5\text{ V}$	1, 3	1 through 8	-10		μA
			2		-100		
			1	9 through 22	-200		
			2, 3		-300		
Logic supply current	$+I_L$	$V_{IN} = 0\text{ V}, 5\text{ V}$	1, 3	1 through 8		10	μA
			2			100	
			1	9 through 22		-200	
			2, 3			-300	
Reference supply current	$+I_R$	$V_{IN} = 0\text{ V}, 5\text{ V}$	1, 3	1 through 8	-10		μA
			2		-100		
			1	9 through 22	-200		
			2, 3		-300		
Turn-on time	t_{on}		11	1 through 8		375	ns
			9			450	
			10			550	
			11	9 through 22		450	
			9			500	
			10			800	

See footnotes at end of table.

STANDARDIZED
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

REVISION LEVEL
F

81006

SHEET
6

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions $-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$, $V_{CC} = \pm 15\text{ V}$ unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Turn-off time	t_{off}		11	1 through 8		250	ns
			9			250	
			10			400	
			11	9 through 22		350	
			9			450	
			10			600	
Single channel isolation <u>2/</u>	V_{ISO}	$R_L = 100\Omega$, $f = 100\text{ kHz}$, $V_{\text{IN}} = 2\text{ V}_{\text{p-p}}$, $C_L = 5\text{ pF}$, $T_A = +25^{\circ}\text{C}$	9	All	60		dB
Crosstalk between channels <u>2/</u>	V_{CT}	$R_L = 100\Omega$, $C_L = 5\text{ pF}$, $f = 100\text{ kHz}$, $V_{\text{IN}} = 2\text{ V}_{\text{p-p}}$, $T_A = +25^{\circ}\text{C}$	9	All	60		dB
Charge transfer <u>2/</u> error	V_{CTE}	$V_{\text{IN}} = 0\text{ V}$, $C_L = 10\text{ nF}$, $T_A = +25^{\circ}\text{C}$	9	All		30	mV
Break before make <u>2/</u> time delay	t_{D}	$T_A = +25^{\circ}\text{C}$	9	03,04, 07	5		ns
Driver input <u>2/</u> capacitance	C_A	$V_{\text{IN}} = 0\text{ V}$, $T_A = +25^{\circ}\text{C}$	9	All		45	pF
Switch input <u>2/</u> capacitance	C_{IS}	Switch off, $T_A = +25^{\circ}\text{C}$	9	All		60	pF
Switch output <u>2/</u> capacitance	C_{OS}	Switch off, $T_A = +25^{\circ}\text{C}$	9	All		60	pF

1/ The listed resistance limits correspond to the following voltage values:

45 Ω and 75 Ω - $\pm 9.25\text{ V}$, $\pm 6.75\text{ V}$

50 Ω and 150 Ω - $\pm 8.50\text{ V}$, $\pm 6.0\text{ V}$

2/ If not tested shall be guaranteed at the specified limits.

STANDARDIZED
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A


REVISION LEVEL
F

81006

SHEET
7


Device type 01 only

Case A




Device types 01 and 09

Case E




Device types 09 only

Case I




Device type 02 only

Case A



Device types 02, 10, and 19

Case E



Device types 02 and 10

Case I




FIGURE 1. Terminal connections.

STANDARDIZED
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A


81006

REVISION LEVEL
F

SHEET
8


Device type 03 only

Case A




Device types 03, 11, and 21

Case E




Device type 04 only

Case A



Device types 12 and 22

Case E



Case 2




FIGURE 1. Terminal connections - Continued.

STANDARDIZED
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A


81006

REVISION LEVEL
F

SHEET
9


Device type 05 only

Case A




Device types 05 and 13

Case E




Case I




Device type 06 only

Case A



Device types 06, 14, and 20

Case E



Device types 14 and 20

Case 2




FIGURE 1. Terminal connections - Continued.

STANDARDIZED
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A


81006

REVISION LEVEL
F

SHEET
10


Device type 07 only

Case A




Device types 07, 15, and 17

Case E



Device type 08 only

Case A



Device types 08, 16, and 18

Case E




FIGURE 1. Terminal connections - Continued.

STANDARDIZED
MICROCIRCUIT DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

81006

REVISION LEVEL
F

SHEET
11

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (in accordance with method 5005, table I)
Interim electrical parameters (method 5004)	---
Final electrical test parameters (method 5004)	1*, 2, 3
Group A test requirements (method 5005)	1, 2, 3, 9, 10, 11
Groups C and D end-point electrical parameters (method 5005)	1

* PDA applies to subgroup 1.

3.8 Notification of change. Notification of change to DESC-EC shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.9 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

- a. Burn-in test, method 1015 of MIL-STD-883.
 - (1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015 of MIL-STD-883.
 - (2) $T_A = +125^{\circ}\text{C}$, minimum.
- b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. Subgroups 4, 5, 6, 7, and 8 in table I, method 5005 of MIL-STD-883 shall be omitted.

STANDARDIZED MICROCIRCUIT DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		81006
		REVISION LEVEL F	SHEET 12

4.3.2 Groups C and D inspections.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test conditions, method 1005 of MIL-STD-883.
 - (1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005 of MIL-STD-883.
 - (2) $T_A = +125^\circ\text{C}$, minimum.
 - (3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for original equipment manufacturer application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Replaceability is determined as follows:

- a. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.
- b. When a QPL source is established, the device specified in this drawing will be replaced by the microcircuit identified as PIN M38510/10501BXX-----/10508BXX.

6.3 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished in accordance with MIL-STD-481 using DD Form 1693, Engineering Change Proposal (Short Form).

6.4 Record of users. Military and industrial users shall inform Defense Electronics Supply Center when a system application requires configuration control and the applicable SMD. DESC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronics devices (FSC 5962) should contact DESC-EC, telephone (513) 296-6047.

6.5 Comments. Comments on this drawing should be directed to DESC-EC, Dayton, Ohio 45444, or telephone (513) 296-5377.

6.6 Approved sources of supply. Approved sources of supply are listed in MIL-BUL-103. The vendors listed in MIL-BUL-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DESC-EC.

STANDARDIZED MICROCIRCUIT DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		81006
		REVISION LEVEL F	SHEET 13

STANDARDIZED MILITARY DRAWING SOURCE APPROVAL BULLETIN

DATE: 92-11-24

Approved sources of supply for SMD 81006 are listed below for immediate acquisition only and shall be added to MIL-BUL-103 during the next revision. MIL-BUL-103 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DESC-EC. This bulletin is superseded by the next dated revision of MIL-BUL-103.

Military drawing PIN	Vendor CAGE number	Vendor similar PIN <u>1</u> /	Replacement military specification PIN
8100601AX <u>2</u> /			M38510/10501BAX
8100601EX <u>3</u> /	1ES66	IH5040MJE/883B	M38510/10501BEX
	17856	DG5140AK	
8100602AX <u>2</u> /			M38510/10502BAX
8100602EX <u>3</u> /	1ES66	IH5041MJE/883B	M38510/10502BEX
	17856	DG5141AK	
8100602IX	17856	DG5141AA	M38510/10502BIX
8100603AX <u>2</u> /			M38510/10503BAX
8100603EX <u>3</u> /	1ES66	IH5042MJE/883B	M38510/10503BEX
	17856	DG5142AK	
8100604AX <u>2</u> /			M38510/10504BAX
8100604EX <u>3</u> /	34371	IH5043MJE	M38510/10504BEX
	1ES66	IH5043MJE/883B	
	17856	DG5143AK	
8100605AX <u>2</u> /			M38510/10505BAX
8100605EX <u>3</u> /	1ES66	IH5044MJE/883B	M38510/10505BEX
	17856	DG5144AK	
8100605IX	17856	DG5144AA	M38510/10505BIX
8100606AX	1ES66	IH5045MFD/883B	M38510/10506BAX
8100606EX <u>3</u> /	1ES66	IH5045MJE/883B	M38510/10506BEX
	17856	DG5145AK	
8100607AX <u>2</u> /			M38510/10507BAX
8100607EX <u>2</u> /			M38510/10507BEX
8100608AX <u>2</u> /			M38510/10508BAX
8100608EX	1ES66	IH5047MJE/883B	M38510/10508BEX
8100609EX <u>3</u> /	1ES66	IH5140MJE/883B	M38510/10501BEX
	34371	HI1-5040/883	
8100609IX <u>2</u> /			M38510/10501BIX
8100610EX <u>3</u> /	1ES66	IH5141MJE/883B	M38510/10502BEX
	34371	IH5141MJE	
	34371	HI1-5041/883	
8100610IX <u>2</u> /			M38510/10502BIX
8100611EX <u>3</u> /	1ES66	IH5142MJE/883B	M38510/10503BEX
	34371	IH5142MJE	
	34371	HI1-5042/883	
8100612EX <u>3</u> /	1ES66	IH5143MJE/883B	M38510/10504BEX
	32293	IH5143MJE	
	34371	HI1-5043/883	
81006122X	34371	HI4-5043/883	---

See footnotes at end of table.

STANDARDIZED MILITARY DRAWING SOURCE APPROVAL BULLETIN - Continued.

Military drawing PIN	Vendor CAGE number	Vendor similar PIN <u>1/</u>	Replacement military specification PIN
8100613EX <u>3/</u>	1ES66	IH5144MJE/883B	M38510/10505BEX
	34371	IH5144MJE	
	34371	HI1-5044/883	
8100613IX <u>2/</u>			M38510/10505BIX
8100614EX <u>3/</u>	1ES66	IH5145MJE/883B	M38510/10506BEX
	34371	IH5145MJE	
	34371	HI1-5045/883	
81006142X	34371	HI4-5045/883	---
8100615EX	34371	HI1-5046/883	M38510/10507BEX
8100616EX	1ES66	IH5047MJE/883B	M38510/10508BEX
	34371	HI1-5047/883	
8100617EX	34371	HI1-5046A/883	---
8100618EX	34371	HI1-5047A/883	---
8100619EX	1ES66	IH5148MJE/883B	---
	34371	HI1-5048/883	
8100620EX	1ES66	IH5149MJE/883B	---
	34371	HI1-5049/883	
81006202X	34371	HI4-5049/883	---
8100621EX	1ES66	IH5150MJE/883B	---
	34371	HI1-5050/883	
8100622EX	34371	IH5151MJE	---
	34371	HI1-5051/883	
	1ES66	IH5151MJE/883B	
81006222X	34371	HI4-5051/883	---

- 1/ Caution. Do not use this number for item acquisition.
Items acquired to this number may not satisfy the performance requirements of this drawing.
- 2/ No longer available from an approved source.
- 3/ Inactive for new design. Use QPL-38510 device.

Vendor CAGE
number

17856

1ES66

34371

Vendor name
and addressSiliconix, Incorporated
2201 Lauralwood Road
Santa Clara, CA 95054Maxim Integrated Products
120 San Gabriel Drive
Sunnyvale, CA 94086Harris Semiconductor
200 Palm Bay Boulevard
P.O. Box 883
Melbourne, FL 32901

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in this information bulletin.